

Description

SEMICOA Corporation offers:

- Screening and processing per MIL-PRF-19500 Appendix E
- JAN level (2N3498J)
- JANTX level (2N3498JX)
- JANTXV level (2N3498JV)
- QCI to the applicable level
- 100% die visual inspection per MIL-STD-750 method 2072 for JANTXV
- Radiation testing (total dose) upon request

Please contact SEMICOA for special configurations
www.SEMICOA.com or (714) 979-1900

Applications

- General purpose
- Low power
- NPN silicon transistor



Features

- Hermetically sealed TO-39 metal can
- Also available in chip configuration
- Chip geometry 5620
- Reference document: MIL-PRF-19500/366

Benefits

- Qualification Levels: JAN, JANTX, and JANTXV
- Radiation testing available

| Absolute Maximum Ratings | | T _C = 25°C unless otherwise specified | |
|--|------------------|--|------------|
| Parameter | Symbol | Rating | Unit |
| Collector-Emitter Voltage | V _{CEO} | 100 | Volts |
| Collector-Base Voltage | V _{CBO} | 100 | Volts |
| Emitter-Base Voltage | V _{EBO} | 6 | Volts |
| Collector Current, Continuous | I _C | 500 | mA |
| Power Dissipation, T _A = 25°C Derate linearly above 25°C | P _T | 1 5.71 | W mW/°C |
| Thermal Resistance | R _{θJA} | 175 | °C/W |
| Operating Junction Temperature | T _J | -65 to +200 | °C |
| Storage Temperature | T _{STG} | -65 to +200 | °C |

ELECTRICAL CHARACTERISTICS

 characteristics specified at $T_A = 25^\circ\text{C}$

Off Characteristics

| Parameter | Symbol | Test Conditions | Min | Typ | Max | Units |
|-------------------------------------|---------------|---|-----|-----|-----|---------------|
| Collector-Emitter Breakdown Voltage | $V_{(BR)CEO}$ | $I_C = 10\text{ mA}$ | 100 | | | Volts |
| Collector-Base Cutoff Current | I_{CBO1} | $V_{CB} = 100\text{ Volts}$ | | | 10 | μA |
| | I_{CBO2} | $V_{CB} = 50\text{ Volts}$ | | | 50 | nA |
| | I_{CBO3} | $V_{CB} = 50\text{ Volts}, T_A = 150^\circ\text{C}$ | | | 50 | μA |
| Collector-Emitter Cutoff Current | I_{CEO} | $V_{CE} = 80\text{ Volts}$ | | | 1 | μA |
| Emitter-Base Cutoff Current | I_{EBO1} | $V_{EB} = 6\text{ Volts}$ | | | 10 | μA |
| | I_{EBO2} | $V_{EB} = 4\text{ Volts}$ | | | 25 | nA |

On Characteristics

 Pulse Test: Pulse Width = 300 μs , Duty Cycle $\leq 2.0\%$

| Parameter | Symbol | Test Conditions | Min | Typ | Max | Units |
|--------------------------------------|--------------|---|---------------------------|-----|-----|-------|
| DC Current Gain | h_{FE1} | $I_C = 0.1\text{ mA}, V_{CE} = 10\text{ Volts}$ | 20 | | | |
| | h_{FE2} | $I_C = 1.0\text{ mA}, V_{CE} = 10\text{ Volts}$ | 25 | | | |
| | h_{FE3} | $I_C = 10\text{ mA}, V_{CE} = 10\text{ Volts}$ | 35 | | | |
| | h_{FE4} | $I_C = 150\text{ mA}, V_{CE} = 10\text{ Volts}$ | 40 | | 120 | |
| | h_{FE6} | $I_C = 500\text{ mA}, V_{CE} = 10\text{ Volts}$ | 15 | | | |
| | h_{FE7} | $I_C = 150\text{ mA}, V_{CE} = 10\text{ Volts}$ | 22 | | | |
| | | | $T_A = -55^\circ\text{C}$ | | | |
| Base-Emitter Saturation Voltage | V_{BEsat1} | $I_C = 10\text{ mA}, I_B = 1\text{ mA}$ | | | 0.8 | Volts |
| | V_{BEsat3} | $I_C = 300\text{ mA}, I_B = 30\text{ mA}$ | | | 1.4 | Volts |
| Collector-Emitter Saturation Voltage | V_{CEsat1} | $I_C = 10\text{ mA}, I_B = 1\text{ mA}$ | | | 0.2 | Volts |
| | V_{CEsat3} | $I_C = 300\text{ mA}, I_B = 30\text{ mA}$ | | | 0.6 | Volts |

Dynamic Characteristics

| Parameter | Symbol | Test Conditions | Min | Typ | Max | Units |
|--|------------|--|-----|-----|-----|-------|
| Magnitude – Common Emitter, Short Circuit Forward Current Transfer Ratio | $ h_{FE} $ | $V_{CE} = 20\text{ Volts}, I_C = 20\text{ mA}, f = 100\text{ MHz}$ | 1.5 | | 8 | |
| Small Signal Short Circuit Forward Current Transfer Ratio | h_{FE} | $V_{CE} = 10\text{ Volts}, I_C = 10\text{ mA}, f = 1\text{ kHz}$ | 35 | | 300 | |
| Open Circuit Output Capacitance | C_{OBO} | $V_{CB} = 10\text{ Volts}, I_E = 0\text{ mA}, 100\text{ kHz} < f < 1\text{ MHz}$ | | | 10 | pF |
| Open Circuit Input Capacitance | C_{IBO} | $V_{EB} = 0.5\text{ Volts}, I_C = 0\text{ mA}, 100\text{ kHz} < f < 1\text{ MHz}$ | | | 80 | pF |
| Noise Figure | NF_1 | $V_{CE} = 10\text{ Volts}, I_C = 0.5\text{ mA}, f = 1\text{ kHz}, R_g = 1\text{ k}\Omega$ | | | 16 | dB |
| | NF_2 | $V_{CE} = 10\text{ Volts}, I_C = 0.5\text{ mA}, f = 10\text{ kHz}, R_g = 1\text{ k}\Omega$ | | | 6 | dB |

Switching Characteristics

| | | | | | | |
|-------------------------|-----------|---|--|--|-------|----|
| Saturated Turn-On Time | t_{ON} | $V_{EB} = 5\text{ Volts}, I_C = 150\text{ mA}, I_{B1} = 15\text{ mA}$ | | | 115 | ns |
| Saturated Turn-Off Time | t_{OFF} | $I_C = 150\text{ mA}, I_{B1}=I_{B2}=15\text{ mA}$ | | | 1,150 | ns |